



M-Series, 30WATT LED FIXTURE – 120VAC_{input}

Low Profile High Lumen Output LED Downlight
Fully Integrated LED Light Fixture, 10in Fixture

Item Code	Type
Project	
Comments	Date
Prepared by	

SPECIFICATIONS & FEATURES

OVERVIEW – This high performance, high lumen fixture with 120VAC phase or 4-wire SimpleNet digital dimming makes this an ideal fixture for retro-fitting high wattage incandescent or fluorescent lamps from 8 – 24 feet ceiling heights.

WHERE TO USE – Interior or exterior under covered surface, new construction and/or retro-fit installations where surface mount or recessed lighting is required. Install in RM, NC, IC, ICAT & Fire Rated applications.

TYPICAL APPLICATIONS – Commercial, industrial and hospitality applications where general illumination is required. Examples include; breezeways, corridors, atriums, theaters, ballrooms, garages, porte-cochere, warehouses & more.

DESIGN & CONSTRUCTION – Patented low profile planer design utilizing Light Forward Heat Forward thermal management. 100% aluminum with 40% recycled content. Fixture is recyclable. Durable powder coated finish.

MOUNTING/INSTALLATION – *New Construction:* mounts directly into any standard 1900 (4S) or Octagonal JBox. *Retrofit:* mounts directly into any 4" or larger recessed fixture with Silescent single or 2-piece mount kit. *Pendant:* using rigid metal conduit or equivalent into 1900 (4S) or Octagonal J-Box..

CEILING THICKNESS – Up to 3 inches thick (ceiling depths > 3" available as custom).

ULTRA LOW PLENUM – only requires the depth of installed J-Box.

ELECTRICAL – Approved for feed through wiring.

DIMMING – Provides both 120VAC phase dimming (conventional incandescent wall dimmer) and Silescent 4-wire digital SimpleNet control. See Silescent Dimming Capabilities and Compatibility chart at www.silescent.com.

ADVANCED INTELLIGENT LIGHT ENGINE – Active thermal feedback monitors both LED & driver to protect against risk of overheating and assuring expected life.

LISTINGS & COMPLIANCE – UL1598 surface mount listed Canada & US (ETL label), wet location under cover ceiling. IP65 & RoHS compliant.

WARRANTY – 5 year limited warranty, both LED and driver. Full warranty details available at www.silescent.com

MADE IN USA – Both driver and fixture are designed, engineered and manufactured by Silescent Lighting in Ft. Lauderdale FL (ARRA & NAFTA compliant).



Shown with MD3 Diffuser



Shown with MR6 Optic

OPTIONS

FINISH – Powder Coat Finish Standard. Custom plating & colors available (RAL).


INPUT VOLTAGE – 120VAC

WATTAGE LEVELS – Available in 30 watts. Custom wattages or lumen levels available upon request.

LAMP TEMPERATURES (CCT) – 2700, 3000, 3500, & 4000 Kelvin (CRI>80), 5000 Kelvin (65CRI), (5000 Kelvin, CRI>80 available upon request).

OPTICS – Wide area dispersion, 170° or Narrow beam (60 degree cutoff).

TRIM RING STYLES – Round-Flat, Square-Flat.



ELECTRICAL DATA

- **Operating Temp:** -40C to +75C
- **Ambient Temp:** <35C
- **Operating Voltage (LP3):** 103 – 125VAC, 50 / 60 Hz
- **Nominal Voltage:** 120VAC
- **Rated Wattage:** 30 watts (see specified fixture photometrics)

ORDERING INFORMATION

Sample Number: M110C01LP351MD330w

Series	Style/Size	Finish/Color	Driver	Color	Optics	Wattage Levels
M	110	C01	LP3	51	MD3	30w
M - MidBay Fixt.	110 - Round/Flat, 10in 310 - Sqr/Flat, 10in	C01 - PC-White C08 - PC-Black	LP3 - 120VAC _{in}	51 - 5000K (80CRI) 50 - 5000K (65CRI) 40 - 4000K (80CRI) 35 - 3500K (80CRI) 30 - 3000K (80CRI) 27 - 2700K (80CRI)	MD3 - Diffuser MR6 - 60° Cutoff	30w - 30 watts

