



# H3-SERIES HIGH BAY LED FIXTURE – AC<sub>in</sub>

DIMMING, Low Profile Ultra High Lumen LED Fixture  
Fully Integrated LED Light Fixture, 120 watts

Item Code:	Type
Project:	
Comments:	Date
Prepared by:	

## FEATURES & BENEFITS

Ideal solution for high ceiling lighting spaces including industrial warehousing, storage facilities, airport hangers or any other area requiring high lumen, high product reliability.

## SPECIFICATIONS & FEATURES

**OVERVIEW** – This high performance, high lumen fixture with dimming makes this an ideal fixture for retro-fitting high wattage incandescent or fluorescent lamps from 8 – 24 feet ceiling heights.

**WHERE TO USE** – Interior or exterior under covered surface, new construction and/or retro-fit installations where surface mount lighting is required. Install in RM, NC, IC, ICAT & Fire Rated applications.

**TYPICAL APPLICATIONS** – Commercial, industrial and hospitality applications where general illumination is required. Examples include; warehouses, storage facilities, ballrooms, theatres, atriums, garages, porte-cochere & more.

**DESIGN & CONSTRUCTION** – Patented low profile planer design utilizing Light Forward Heat Forward thermal management. 100% aluminum with 40% recycled content. Fixture is recyclable. Durable powder coated finish.

**MOUNTING/INSTALLATION** – *New Construction & Retrofit:* May be mounted into any standard 1900 (4S) or octagonal junction box; chain mounted, or can be pendant mounted using rigid metal conduit or equivalent into 1900 (4S) or Octagonal J-Box.

**DIMMING** – Provides both 120VAC phase dimming (conventional incandescent wall dimmer) and Silescent 4-wire digital SimpleNet control. See Silescent Dimming Capabilities and Compatibility chart at [www.silescent.com](http://www.silescent.com).

**ADVANCED INTELLIGENT LIGHT ENGINE** – Active thermal feedback monitors both LED & driver to protect against risk of overheating and assuring expected life.

**LISTINGS & COMPLIANCE** – UL1598 surface mount listed Canada & US (ETL label). RoHS compliant.

**FIXTURE WEIGHT** – under 10.0 lbs (including mounting)

**WARRANTY** – 5 year limited warranty, both LED and driver. Full warranty details available at [www.silescent.com](http://www.silescent.com)

**MADE IN USA** – Both driver and fixture are designed, engineered and manufactured by Silescent Lighting in Ft. Lauderdale FL (ARRA & NAFTA compliant).




J-Box Mounting with Diffuser Shown

## ELECTRICAL DATA


- **Operating Temp:** -40C to +75C
- **Ambient Temp:** <35C
- **Operating Voltage:**
  - **LP3** 103 – 125VAC, 50 / 60 Hz
  - **HS3/HN3** 208 – 285VAC, 50 / 60 Hz
- **Nominal Voltage:** 120/240/277V (specify)
- **Rated Wattage:** 120watts (see specified fixture photometrics)

## MOUNTING OPTIONS:



Optional J-Box Mount Kit

- Accommodates rigid pipe pendant mount
- H424C01LP350HD3120j



Standard Chain Mounting:

- Chain not included.
- Accommodates Hook and Loop Mounting.
- H424C01LP350HD3120c

## OPTIONS

**FINISH** – Powder Coat Finish Standard. Custom colors available (RAL).

**WATTAGE LEVELS** – Standard 120watt product. Custom wattages or lumen levels available upon request.

**LAMP TEMPERATURES (CCT)** – 2700, 3000, 3500, & 4000 Kelvin (CRI>80), 5000 Kelvin (65CRI), (5000 Kelvin, CRI>80 available upon request).

**OPTICS** – Diffused optic provides wide area dispersion, 170 degree beam spread. MR6 optic provides 60 degree cutoff.

## ORDERING INFORMATION

Sample Number: H324C01LP350HD3120c

Series	Style/Size	Finish/Color	Driver	Color	Optics	Wattage Levels	Mount
H3	24	C01	LP3	50	HD3	120	c
H3 - 120w HighBay	24 - 24in Diameter	C01 - PC-White C08 - PC-Black	LP3 - 120VAC <sub>in</sub> , Phase HS3 - 277VAC <sub>in</sub> , SN	51 - 5000K (80CRI) 50 - 5000K (65CRI) 40 - 4000K (80CRI) 35 - 3500K (80CRI) 30 - 3000K (80CRI) 27 - 2700K (80CRI)	HD3 - 8in Diffuser MR6 - 60° Cutoff	120 - 120 watts	c - Chain j - JBox Mnt

